





LEFT HAND DIGITAL CALIPERS (NON-WATERPROOF)



- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7315-, 7302-, 7305-)



1130-150W




Code	Range	Accuracy	Thumb roller	L	а	b	С	d
1130-150W*	0-150mm/0-6"	±0.03mm	without	236mm	21mm	16mm	16mm	40mm
1130-200W*	0-200mm/0-8"	±0.03mm	without	286mm	24mm	19mm	16mm	50mm
1130-300W*	0-300mm/0-12"	±0.03mm	without	400mm	25mm	20.5mm	16mm	60mm
1130-150*	0-150mm/0-6"	±0.03mm	with	236mm	21mm	16mm	16mm	40mm
1130-200*	0-200mm/0-8"	±0.03mm	with	286mm	24mm	19mm	16mm	50mm
1130-300*	0-300mm/0-12"	±0.03mm	with	400mm	25mm	20.5mm	16mm	60mm

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany

DIGITAL CALIPERS WITH CERAMIC TIPPED JAWS (NON-WATERPROOF)








- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output, made of stainless steel
- Meet ĎIN862
- Optional accessory: data output cable (code **7315-**, **7302-**, **7305-**, for calipers without built-in wireless)



1193-150W



DATA

OUTPUT

Code	Range	Accuracy	Thumb roller	L	a	b	С	d	Wireless
1193-150W *	0-150mm/0-6"	±0.03mm	without	235mm	21mm	16.5mm	16mm	40mm	no
1193-150WWL*	0-13011111/0-6	±0.0311111	Williout	23311111	21111111	10.511111	TOTTITI	40111111	built-in wireless
1193-200W *	0-200mm/0-8"	±0.03mm	without	297mm	24mm	20mm	16mm	50mm	no
1193-200WWL*	0-20011111/0-6	±0.0311111	Williout	297111111	24111111	20111111	TOTTITI	30111111	built-in wireless
1193-300W *	0.200,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	±0.03mm	without	390mm	26mm	21.5mm	16mm	60mm	no
1193-300WWL*	0-300mm/0-12"	±0.0311111	Without	39011111	2011111	21.511111	10111111	OUIIIII	built-in wireless
1193-150*	0.450	±0.03mm	i the	235mm	21mm	16.5mm	16mm	400000	no
1193-150WL*	0-150mm/0-6"	±0.03mm	with	23311111	21mm	10.311111	Tomm	40mm	built-in wireless
1193-200*	0.200,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	±0.03mm	i i la	297mm	24mm	20mm	16mm	E O ma ma	no
1193-200WL*	0-200mm/0-8"	±0.03mm	with	29/111111	24111111	20111111	10111111	50mm	built-in wireless
1193-300*	0.000	.0.00		200	00	04 5	10	00	no
1193-300WL*	0-300mm/0-12"	±0.03mm	with	390mm	26mm	21.5mm	16mm	60mm	built-in wireless

 $^{^{\}star}$ Supplied with manufacturer inspection certificate traceable to DKD Germany

DIGITAL CALIPERS WITH CARBIDE TIPPED JAWS (NON-WATERPROOF)






- Carbide tipped jaws for inside and outside measurements
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7315-, 7302-, 7305-, for calipers without built-in wireless)



1110-150AW



Code	Range	Accuracy	Thumb roller	L	а	b	С	d	Wireless
1110-150AW*	0-150mm/0-6"	±0.03mm	without	236mm	21mm	16mm	16mm	40mm	no
1110-150AWWL*	0-13011111/0-0	±0.0311111	Williout	23011111	21111111	10111111	10111111	40111111	built-in wireless
1110-200AW*	0-200mm/0-8"	±0.03mm	without	286mm	24mm	19mm	16mm	50mm	no
1110-200AWWL*	0-20011111/0-0	±0.0311111	Williout	20011111	24111111	19111111	10111111	3011111	built-in wireless
1110-300AW*	0-300mm/0-12"	±0.03mm	without	400mm	25mm	20.5mm	16mm	60mm	no
1110-300AWWL*	0-30011111/0-12	±0.0311111	Williout	400111111	2311111	20.511111	10111111	OUIIIII	built-in wireless
1110-150A*	0-150mm/0-6"	±0.03mm	with	236mm	21mm	16mm	16mm	40mm	no
1110-150AWL*	0-13011111/0-6	±0.0311111	VVILII	23011111	21111111	10111111	1011111	40111111	built-in wireless
1110-200A*	0-200mm/0-8"	±0.03mm	with	286mm	24mm	19mm	16mm	50mm	no
1110-200AWL*	0-20011111/0-6	±0.0311111	VVILII	20011111	24111111	1911111	10111111	3011111	built-in wireless
1110-300A*	0.200,000,000,000	±0.03mm	with	400mm	25mm	20.5mm	16mm	60mm	no
1110-300AWL*	0-300mm/0-12"	±0.03IIIII	Willi	40011111	2011111	20.311111	10111111	OUTITI	built-in wireless

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany

DIGITAL CALIPERS (NON-WATERPROOF)






■ Buttons: on/off, zero, mm/inch

- Automatic power off, move the digital unit to turn on power
 Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7315-, 7302-, 7305-, for calipers without built-in wireless)







Code	Range	Accuracy	a	С	d	е	L	Wireless
1170-200	0-200mm/0-8"	±0.03mm	12mm	17mm	60mm	10mm	320mm	no
1170-200WL	0-20011111/0-0	±0.0311111	1211111	17111111	Oomin	10111111	32011111	built-in wireless
1170-306	0-300mm/0-12"	±0.04mm	12mm	17mm	60mm	10mm	420mm	no
1170-306WL	0-30011111/0-12	±0.0411111	1211111	17111111	Oomin	10111111	42011111	built-in wireless
1170-300	0-300mm/0-12"	±0.06mm	12mm	17mm	90mm	10mm	420mm	no
1170-300WL	0-30011111/0-12	±0.06111111	12111111	17111111	90111111	10111111	42011111	built-in wireless





DIGITAL CALIPERS (NON-WATERPROOF)




- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power

 Battery CR2032
- Data output
- Made of stainless steel
- Optional accessory: data output cable (code 7315-, 7302-, 7305-, for calipers without built-in wireless)

1171-300





Code	Range	Accuracy	a	b	С	d	е	L	Wireless
1171-200	0-200mm/0-8"	±0.03mm	12mm	38mm	17mm	60mm	10mm	320mm	no
1171-200WL	0 20011111/0 0	20.0011111	1211111	Oomin		00111111	10111111	020111111	built-in wireless
1171-250	0-250mm/0-10"	±0.03mm	12mm	38mm	17mm	60mm	10mm	365mm	no
1171-250WL	0-23011111/0-10	±0.0311111	1211111	Joillii	17111111	OUTIIII	10111111	30311111	built-in wireless
1171-306	0-300mm/0-12"	±0.04mm	12mm	38mm	17mm	60mm	10mm	420mm	no
1171-306WL	0-30011111/0-12	±0.0411111	12111111	Jonnin	17111111	00111111	10111111	42011111	built-in wireless
1171-300	0-300mm/0-12"	±0.06mm	12mm	38mm	17mm	90mm	10mm	420mm	no
1171-300WL	U-300111111/U-12	±0.0011111	12111111	Joillill	17111111	90111111	TOTTITI	42011111	built-in wireless

ATTENTION: NO DATA OUTPUT


- Resolution: 0.01mm/0.0005"
- Buttons: zero, mm/inch, on/off
- Automatic power off, move the digital unit to turn on power
- Battery LR44
- Meet DIN862
- Made of stainless steel

Code	Range	Accuracy	L
1111-75A	0-75mm/0-3"	±0.02mm	144mm
1111-100A	0-100mm/0-4"	±0.02mm	170mm

MINI DIGITAL CALIPERS (NON-WATERPROOF)



1111-100A



ATTENTION: NO DATA OUTPUT


- Made of hard plastic, non-magnetic and non electric conductive
- Prevent workpieces from scratching by calipers
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Battery CR2032, automatic power off

Code	Range	Accuracy
1139-150	0-150mm/0-6"	±0.1mm

PLASTIC DIGITAL CALIPER (NON-WATERPROOF)



1139-150



WIRELESS DIGITAL CALIPERS (NON-WATERPROOF)










1113-150W

- Built-in wireless data transfer module, Zigbee signal
- Transfer distance is 6 meter
 Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch, data transmission
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Made of stainless steel
- Optional accessory: receiver (code **7315-2**, **7315-3**)





Code	Range	Accuracy	Thumb roller	L	а	b	С	d
1113-150W *	0-150mm/0-6"	±0.03mm	without	236mm	21mm	16mm	16mm	40mm
1113-200W *	0-200mm/0-8"	±0.03mm	without	286mm	24mm	19mm	16mm	50mm
1113-300W *	0-300mm/0-12"	±0.03mm	without	400mm	25mm	20.5mm	16mm	60mm
1113-150*	0-150mm/0-6"	±0.03mm	with	236mm	21mm	16mm	16mm	40mm
1113-200*	0-200mm/0-8"	±0.03mm	with	286mm	24mm	19mm	16mm	50mm
1113-300*	0-300mm/0-12"	±0.03mm	with	400mm	25mm	20.5mm	16mm	60mm

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany

WATERPROOF DIGITAL CALIPERS

ATTENTION: IT IS NECESSARY TO SET ZERO AFTER POWER ON EACH TIME

ATTENTION: NO DATA OUTPUT






1118-150BW



- IP67 dust/waterproof
- Resolution: 0.01mm/0.0005"
- Button function: zero, on/off, mm/inch, ABS/REL, hold
- Battery CR2032
- Meet DIN862
- Made of stainless steel



Code	Range	Accuracy	Thumb roller	L	а	b	С	d
1118-150BW*	0-150mm/0-6"	±0.03mm	without	236mm	21mm	16mm	16mm	40mm
1118-200BW *	0-200mm/0-8"	±0.03mm	without	286mm	24mm	19mm	16mm	50mm
1118-300BW*	0-300mm/0-12"	±0.03mm	without	400mm	25mm	20.5mm	17mm	60mm
1118-150B*	0-150mm/0-6"	±0.03mm	with	236mm	21mm	16mm	16mm	40mm
1118-200B*	0-200mm/0-8"	±0.03mm	with	286mm	24mm	19mm	16mm	50mm
1118-300B*	0-300mm/0-12"	±0.03mm	with	400mm	25mm	20.5mm	17mm	60mm

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany



■ IP67 dust/waterproof ■ Resolution: 0.01mm/0.0005"

■ Made of stainless steel

■ Button function: zero, on/off, mm/inch

■ Large display

■ Battery CR2032





WATERPROOF DIGITAL CALIPERS




1126-150

11 76	
N 50 70 70	19 to 19 m MISSIES (PS)

Code	Range	Accuracy	L	а	b	С	d
1126-150 *	0-150mm/0-6"	±0.03mm	234mm	20mm	15mm	16mm	40mm
1126-200 *	0-200mm/0-8"	±0.03mm	286mm	24mm	19mm	16mm	50mm
1126-300 *	0-300mm/0-12"	±0.03mm	390mm	26mm	21.5mm	16mm	60mm

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany








- Zinc alloy housing for digital unit
- Resolution: 0.01mm/0.0005"
- Buttons: zero, on/off, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Meet DIN862
- Made of stainless steel

DIGITAL CALIPERS (NON-WATERPROOF)



1114-150AW

Code	Range	Accuracy	Thumb roller	L	а	b	С	d
1114-150AW*	0-150mm/0-6"	±0.03mm	without	236mm	21mm	16mm	16mm	40mm
1114-200AW*	0-200mm/0-8"	±0.03mm	without	286mm	24mm	19mm	16mm	50mm
1114-300AW*	0-300mm/0-12"	±0.03mm	without	400mm	25mm	20.5mm	17mm	60mm
1114-150A*	0-150mm/0-6"	±0.03mm	with	236mm	21mm	16mm	16mm	40mm
1114-200A*	0-200mm/0-8"	±0.03mm	with	286mm	24mm	19mm	16mm	50mm
1114-300A*	0-300mm/0-12"	±0.03mm	with	400mm	25mm	20.5mm	17mm	60mm



^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany






DIGITAL CALIPERS (STANDARD TYPE, NON-WATERPROOF)

- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code **7315-**, **7302-**, **7305-**)



1108-150W

Code	Range	Accuracy	Thumb roller	L	а	b	С	d
1108-150W *	0-150mm/0-6"	±0.02mm	without	236mm	21mm	16mm	16mm	40mm
1108-200W *	0-200mm/0-8"	±0.03mm	without	286mm	24mm	19mm	16mm	50mm
1108-250W *	0-250mm/0-10"	±0.03mm	without	350mm	25mm	20.5mm	16mm	60mm
1108-300W *	0-300mm/0-12"	±0.03mm	without	400mm	25mm	20.5mm	16mm	60mm
1108-150*	0-150mm/0-6"	±0.02mm	with	236mm	21mm	16mm	16mm	40mm
1108-200*	0-200mm/0-8"	±0.03mm	with	286mm	24mm	19mm	16mm	50mm
1108-250*	0-250mm/0-10"	±0.03mm	with	350mm	25mm	20.5mm	16mm	60mm
1108-300*	0-300mm/0-12"	±0.03mm	with	400mm	25mm	20.5mm	16mm	60mm



 $^{^{\}star}$ Supplied with manufacturer inspection certificate traceable to DKD Germany

+INSIZE+


HEAVY DUTY 300mm DIGITAL CALIPERS (NON-WATERPROOF)





- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7315-, 7302-, 7305-)





Code	Range	Thumb roller	Accuracy		
1196-300W*	0-300mm/0-12"	without	±0.03mm		
1196-300 *	0-300mm/0-12"	with	±0.03mm		

^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany

METRIC DIGITAL CALIPERS (NON-WATERPROOF)








- Resolution: 0.01mm
- Buttons: on/off, zero, hold
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7315-, 7302-, 7305-)



1109-150W

Code	Range	Accuracy	Thumb roller	L	а	b	С	d
1109-150W *	0-150mm	±0.03mm	without	236mm	21mm	16mm	16mm	40mm
1109-200W *	0-200mm	±0.03mm	without	286mm	24mm	19mm	16mm	50mm
1109-300W *	0-300mm	±0.03mm	without	400mm	25mm	20.5mm	16mm	60mm
1109-150*	0-150mm	±0.03mm	with	236mm	21mm	16mm	16mm	40mm
1109-200*	0-200mm	±0.03mm	with	286mm	24mm	19mm	16mm	50mm
1109-300*	0-300mm	±0.03mm	with	400mm	25mm	20.5mm	16mm	60mm



DIGITAL CALIPERS WITH ROUND DEPTH BAR (NON-WATERPROOF)






- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032
- Data output
- Meet DIN862
- Made of stainless steel
- Optional accessory: data output cable (code 7315-, 7302-, 7305-, for calipers without built-in wireless)





1119-150W

									(mm)
Code	Range	Accuracy	Thumb roller	L	а	b	С	d	Wireless
1119-150W *	0-150mm/0-6"	±0.03mm	without	236	21	16	16	40	no
1119-150WWL*									built-in wireless
1119-150*	0-150mm/0-6"	±0.03mm	with	236	21	16	16	40	no
1119-150WL*							10	40	built-in wireless



^{*}Supplied with manufacturer inspection certificate traceable to DKD Germany

 $^{{}^{}ullet}$ Supplied with manufacturer inspection certificate traceable to DKD Germany