



1726 / 1728 DIGI-MET® Indicators



1726 502



1728 502

Model

- Aluminium housing
- Hardened stainless steel spindle
- Outer ring (Bezel) Ø 60 mm
- Replacement probe tip M 2.5
- Protection class IP42
- Clamping shank Ø 8 mm
- Display unit can be rotated through 280°
- LCD display with 11 mm high numerals
- Factory standard

Functions

- ON / OFF
- Quick-Start**
- Quick-Lock** (key lock)
- Set to zero at any point
- mm / inch switching
- ABS (display can be set to zero without losing the Preset value)
- TOL (tolerance value input)
- Reversal of counting direction
- Factor input

Delivery

- Cardboard box

⏏	📏	Measuring span		Resolution		Error limit		Repeatability	Measuring force	Order no.	List price
		mm		mm	inch	total span mm	partial span** mm				
Reading 0.001 mm											
		12.5		0.001*	.00005	0.004	0.002	0.001	0.65 - 0.9	1726 502	345.00
		25		0.001*	.00005	0.004	0.002	0.001	0.65 - 1.15	1726 506	380.00
		50		0.001*	.00005	0.007	0.002	0.001	1.25 - 2.7	1726 510	669.00
		100		0.001*	.00005	0.008	0.002	0.001	1.6 - 3.5	1726 514	828.00
Reading 0.01 mm											
		12.5		0.01	.0005	0.02		0.01	0.65 - 0.9	1728 502	289.00
		25		0.01	.0005	0.02		0.01	0.65 - 1.15	1728 506	368.00
		50		0.01	.0005	0.02		0.01	1.25 - 2.7	1728 510	600.00
		100		0.01	.0005	0.02		0.01	1.6 - 3.5	1728 514	768.00

* Reading switchable: 0.0005 / 0.001 / 0.002 / 0.005 / 0.010 mm

** Partial span = 25 steps by step value 0.0005 mm



1998720

1998501

1997501

Accessories

	Order no.	List price
Battery, 3V-Lithium, CR 2450	1998 770	5.90
Data cable Data Variable to USB	1998 720	72.00
Data cable Data Variable to RS232	1997 501	50.00
Data cable Data Variable to digimatic	1998 501	64.00
Cable release (12,5 mm)	1739 910	40.00



= QuickLock



= QuickStart



= Waterproof acc. IP



= Data output



= DIN