



1866 Digital micrometers IP65



1866 410



1866 510



Model

- Reading: 0.001 mm / .00005 inch
- Protection class IP65
- LCD display: 10 mm
- Rapid drive
- Carbide measuring faces
- Spindle stainless, hardened and smoothed
- Frame lacquered
- Thermally insulated
- Factory standard

Functions

- ON / OFF
- **Quick-Start**
- **Quick-Lock** (key lock)
- Set to zero at any point
- mm / inch switching
- ABS (display can be set to zero without losing the ORIGIN)
- Hold

▪ Additionally 1866 5xx:

- ORIGIN (Preset value)
- Variable data output USB + Digimatic
- TOL (tolerance value input)

Delivery

- Plastic case
- From measuring range 25 mm upwards includes a setting standard

✕	📏	Measuring range		Pitch mm	Spindle dia. mm	Error limit mm	Order no.	List price EUR
		mm	inch					
Without data output								
		0 - 25	0 - 1	0.5	6.5	0.002	1866 410	207.00
		25 - 50	1 - 2	0.5	6.5	0.002	1866 413	270.00
		50 - 75	2 - 3	0.5	6.5	0.003	1866 417	343.00
		75 - 100	3 - 4	0.5	6.5	0.003	1866 420	391.00
With DataVariable bidirectional								
		0 - 25	0 - 1	0.5	6.5	0.002	1866 510	249.00
		25 - 50	1 - 2	0.5	6.5	0.002	1866 513	299.00
		50 - 75	2 - 3	0.5	6.5	0.003	1866 517	389.00
		75 - 100	3 - 4	0.5	6.5	0.003	1866 520	435.00



1998725

1998802

Accessories

	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable bidirectional DataVariable to USB	1998 801	98.00
Data cable bidirectional DataVariable to Digimatic	1998 802	85.00