



HELIOS · PREISSER

1866i Digital micrometers IP65 with integrated wireless



1866 41060



**integrated  
iW wireless**  
Wireless Data Transmission

2

**Model**

- Reading: 0.001 mm / .00005 inch
- Protection class IP65
- LCD display: 10 mm
- Rapid drive
- Carbide measuring faces
- Spindle stainless, hardened and smoothed
- Frame lacquered
- Thermally insulated
- Factory standard

**Functions**

- ON / OFF
- **Quick-Start**
- **Quick-Lock** (key lock)
- Set to zero at any point
- mm / inch switching
- ABS (display can be set to zero without losing the ORIGIN)
- Hold
- ORIGIN (Preset value)
- TOL (tolerance value input)
- Integrated Wireless

**Delivery**

- Plastic case
- From measuring range 25 mm upwards includes a setting standard

Measuring range	Measuring range		Pitch	Spindle dia.	Error limit	Order no.	List price
	mm	inch					
0 - 25	0 - 1	0.5	6.5	0.002	1866 41060	259.00	
25 - 50	1 - 2	0.5	6.5	0.002	1866 41360	319.00	
50 - 75	2 - 3	0.5	6.5	0.003	1866 41760	389.00	
75 - 100	3 - 4	0.5	6.5	0.003	1866 42060	435.00	

**Accessories**

	Order no.	List price
		EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
i-Stick USB-receiver for Integrated Wireless	1998 780	95.00



1998780

More information on our i-series and Integrated Wireless on page 252

Integrated Wireless is intended to be sold within the European Economic Area only