



1866 Digital micrometer BASIC











Model

- Reading: 0.001 mm / .00005 inch
- Protection class IP40
- LCD display: 10 mm
- Rapid drive
- Carbide measuring faces
- Spindle stainless, hardened and smoothed
- Frame lacquered
- Thermally insulated
- Factory standard

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- Hold

Delivery

Plastic case

М	Measuring range		Pitch	Spindle dia.	Error limit	Order no.	List price
	mm	inch	mm	mm	mm		EUR
	0 - 25	0 - 1	0.5	6.5	0.002	1866 210	175.00

Accessories	Order no.	List price	
		EUR	
Battery, 3V-Lithium, CR 2032	0220 704	3.90	

1866i Sets of digital micrometers





Delivery

- Plastic case
- From measuring range 25 mm upwards includes a setting standard

₩	Measuring range		Spindle dia.	Order no.	List price	
	mm	inch	mm		EUR	
With Inte	grated Wirele	ess				
	0 - 100	0 - 4	6.5	1866 42160	1390.00	
With Dat	aVariable bidi	rectional				
	0 - 100	N - 4	6.5	1866 521	1360.00	

Accessories	Order no.	List price EUR
Battery, 3V-Lithium, CR 2032	0220 704	3.90
Data cable bidirectional DataVariable to USB	1998 801	98.00
Data cable bidirectional DataVariable to Digimatic	1998 802	85.00
i-Stick USB-receiver for Integrated Wireless	1998 780	95.00



