



1367 DIGI-MET® Offset depth gauges
















Model

- Stainless steel
- Inductive measuring system, protection class IP67
- LCD display 7.5 mm
- Factory standard
- Housing and operating keys have an excellent chemical resistance
- Locking screw

Functions

- ON / OFF
- Quick-Start
- Quick-Lock (key lock)
- Set to zero at any point
- mm / inch switching
- Variable data output RS 232 + Digimatic + USB

Delivery

- Up to 300 mm measuring range in plastic case
- From 500 mm measuring range in wooden case
- Screw-on extended measuring bridges must be ordered separately (page 53)

M		Measuring range		Length of beam	Reading		Error limit	Order no.	List price
		mm	inch	mm	mm	inch	mm		EUR
•		0 - 200	0 - 8	100	0.01	.0005	0.03	1367 718	476.00
		0 - 300	0 - 12	150	0.01	.0005	0.03	1367 722	575.00
		0 - 500	N - 2N	150	N N1	0005	N N3	1367 728	724 NN



Accessories	Order no.	List price EUR
Data cable DATA VARIABLE to RS232	1997 501	57.00
Data cable DATA VARIABLE to digimatic	1998 501	73.00
Data cable DATA VARIABLE to USB	1998 720	82.00

