Digital depth micrometers

Digital depth micrometers with interchangeable, spherical rods, because of which beveled and hollow surfaces can be measured very accurately. The high accuracy of the rods makes resetting after exchanging the rods unnecessary. Two models with different base lengths available.

- Measuring range: 0-300 mm.
- Resolution: 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- Automatic switch-off.

- Preset.
- Interchangeable measuring rods.
- Locking screw.
- DIN 863 T2.
- Power supply: 1 battery (V357).





| Item No. | Measuring range/mm | Accuracy/mm | Number of rods | Price EUR |
|------------|--------------------|-------------|----------------|-----------|
| Base 63 m | m: | | | |
| 906.982 | 0 - 25 | ± 0.004 | 1 | |
| 906.983 | 0- 50 | ± 0.004 | 2 | |
| 906.984 | 0 - 100 | ± 0.005 | 4 | |
| 906.985 | 0-150 | ± 0.005 | 6 | |
| 906.986 | 0-200 | ± 0.006 | 8 | |
| 906.987 | 0-300 | ± 0.007 | 12 | |
| Base 101.5 | mm: | | | |
| 906.988 | 0 - 25 | ± 0.004 | 1 | |
| 906.989 | 0- 50 | ± 0.004 | 2 | |
| 906.990 | 0 - 100 | ± 0.005 | 4 | |
| 906.991 | 0 - 150 | ± 0.005 | 6 | |
| 906.992 | 0-200 | ± 0.006 | 8 | |
| 906.993 | 0-300 | ± 0.007 | 12 | |
| Option: | | | | |
| _ | pare battery | | | |

© 2007, Schut Geometrische Meettechniek bv

105

Measuring instruments and systems 2007/2008

Depth micrometers

Depth micrometers with interchangeable, spherical or flat rods. With the flat rods mainly flat and spherical surfaces can be measured very accurately. The spherical rods are especially suitable for beveled and hollow surfaces. The high accuracy of the rods makes resetting after exchanging the rods unnecessary. Two models with different base lengths available.

- Measuring range: 0 300 mm.
- Graduation: 0.01 mm.

- Interchangeable measuring rods.
- Locking screw.
- DIN 863 T2.



Model with spherical rods especially for hollow and beveled surfaces

| Item No. | Price EUR | Item No. | Price EUR | Measuring range/mm | Accuracy mm | Number of rods |
|----------------------------|--------------|----------|--------------|--------------------|----------------|----------------|
| Base 63 mm: Base 101.5 mm: | | | | | | |
| 906.964 | | 906.040 | | 0 - 25 | ± 0.004 | 1 |
| 906.965 | | 906.039 | | 0- 50 | ± 0.004 | 2 |
| 906.966 | | 906.041 | | 0 - 100 | ± 0.005 | 4 |
| 906.967 | | 906.042 | | 0-150 | ± 0.005 | 6 |
| 906.968 | | 906.043 | | 0-200 | ± 0.006 | 8 |
| 906.969 | | 906.044 | | 0-300 | ± 0.007 | 12 |

Model with flat rods especially for flat and spherical surfaces

| Item No. | Price EUR | Item No. | Price EUR | Measuring range/mm | Accuracy mm | Number of rods |
|----------------------------|--------------|----------|--------------|--------------------|----------------|----------------|
| Base 63 mm: Base 101.5 mm: | | | | | | |
| 906.970 | | 906.976 | | 0 - 25 | ± 0.004 | 1 |
| 906.971 | | 906.977 | | 0- 50 | ± 0.004 | 2 |
| 906.972 | | 906.978 | | 0 - 100 | ± 0.005 | 4 |
| 906.973 | | 906.979 | | 0 - 150 | ± 0.005 | 6 |
| 906.974 | | 906.980 | | 0-200 | ± 0.006 | 8 |
| 906.975 | | 906.981 | | 0-300 | ± 0.007 | 12 |