## Universal digital bevel protractor

This digital bevel protractor displays both decimal degrees and degrees-minutes-seconds at the same time.

- Measuring range: -360° to +360°.
- $\blacksquare$  Resolution: 0.008° and 30".
- Accuracy:  $\pm 5'$  or  $\pm 0.08^{\circ}$ .
- Mode: 0-90°, 0-180° or 0-360°.
- On/off switch.
- Reset/preset.

- Reversible measurement direction.
- Fine adjustment.
- Power supply: 1 battery (CR2032).
- Delivery in a case with three blades (150, 200 and 300 mm), a square and an acute angle attachment.



Item No. 1	Description	Price EUR
907.885 1	Bevel protractor	
Option:		
495.157	Spare battery	

### Single blades

Item No.	Blade length/mm	Price EUR
907.911	150	
907.912	200	
907.913	300	



## Universal digital bevel protractors

Digital bevel protractors made of stainless steel, with blades of 150, 200, 300 or 500 mm. The blades and all the measuring faces are hardened.

■ Measuring range (switchable): 1x 360°,

2x 180°, 4x 90°.

■ Resolution: 1', or decimal 0.01°.

■ Accuracy: ±2'.

■ Control with 2 keys for several functions.

■ Indication switchable from degrees and minutes to decimal degrees.

 Automatic switch-off after 10 minutes of idle time with storage of the displayed measuring value.

■ Reset.

■ Opto-RS232C data output.

■ Power supply: 1 battery (CR2032).

#### **Complete bevel protractors**

Blade length/mm	Price EUR
150 200	
300	
	150 200


#### **Options:**

495.157 Spare battery 856.694 Prism base 856.695 Ledge

781.887 Opto-RS232C cable



#### Single blades



Schut

© 2007, Schut Geometrische Meettechniek bv

340

Measuring instruments and systems 2007/2008

## Universal digital bevel protractor

This stainless steel, digital bevel protractor is available with blades from 150 to 1000 mm. The blades and all the measuring faces are hardened.

■ Measuring range: -360°/+360°.

■ Resolution: 1', or decimal 0.01°.

■ Accuracy: ±2'.■ Repeatability: 1'.

■ Control with 5 keys for several functions.

■ Indication switchable from degrees and minutes to decimal degrees.

■ Reset/preset/hold functions.

■ On/off switch.

+ and - direction reversible.

■ Per 90° adjustable.

■ With fine adjustment.

■ Data output, Mitutoyo Digimatic compatible.

■ Delivery of bevel protractor without blade.

■ Power supply: 1 battery (CR2032).

Item No. Description	Price EUR
855.820 Bevel protractor	

#### Single blades

Item No.	Blade length/mm	Price EUR
855.821	150	
855.822	200	
855.823	300	
855.824	500	
855.825	600	
855.826	800	
855.827	1000	

#### **Options:**

495.157 Spare battery 905.409 Data cable 2 m



### **TESA** dial bevel protractor ■ Hardened, stainless steel construction. ■ Measuring range: 4x90°. ■ Dial displays degrees in multiples of 10° in a small window and minutes, with an interval of 5', on main scale. ■ Blade length: 200 or 300 mm. ■ Base and acute angle attachment are optional. ■ Delivery in a case, with 779.391 779.392 1 blade and a declaration of Item No. Description Price EUR conformity. 779.393 Bevel protractor, blade 200 mm Bevel protractor, 779.394 blade 300 mm **Options:** 779.391 Acute angle attachment 779.392 Base 779.395 Additional blade 200 mm 779.396 Additional blade 300 mm Schut Schut **Dial bevel protractor** ■ Hardened, stainless steel construction. ■ Measuring range: 4x90°. ■ Dial displays degrees in multiples of 10° in a small window and minutes, with an interval of 5', on main scale. ■ Blade length: 300 mm. ■ Delivery includes acute angle attachment. Item No. Description Price EUR 906.504 Dial bevel protractor

## **Bevel protractor with magnifier**

- Measuring range: 4 x 90°.
- Vernier: 5', parallax-free.
- With fine adjustment.
- Hardened, stainless steel construction.
- No-glare satin chrome finished scale.
- Blade: 300 mm.
- Delivery in a case with adjustable attachment for acute angles.





Item No. Description

Price EUR

906.502 Bevel protractor with magnifier

# Bevel protractor with magnifier

- Measuring range: 4 x 90°.
- Vernier: 5', parallax-free.
- With fine adjustment.
- Hardened, stainless steel construction.
- No-glare satin chrome finished scale.
- Blades: 150 and 300 mm.
- Delivery in a case with adjustable attachment for acute angles.





Price EUR

855.801 Bevel protractor with magnifier



#### **PROTRACTORS**

## Bevel protractor with magnifier

Universal protractor with micrometer screw adjustment. One rotation of the screw corresponds to an angular change of  $1^{\circ}$ .

- Stainless steel construction, main parts are hardened.
- Complete with reference square for checking bevel protractor.

■ Measuring range: 4 x 90°.

■ Scale graduation: 1'.

■ It is possible to adjust blade and scale by retracting the micrometer screw.

■ Two interchangeable blades of 150 and 300 mm.

■ Delivery in a case.




Item No. Blade length/mm Price EUR 855.811 150 and 300

## **Combination square set**

- Measuring range:  $0 180^{\circ} (90^{\circ} 0^{\circ} 90^{\circ})$ .
- Reading: 1°.
- Scriber (included in square head).
- Double graduation.
- Rotatable.
- Protractor head and square head both fitted with a spirit level.
- Delivery with protractor head, square head, center head, and ruler with mm/mm graduation.







#### **PROTRACTORS**

## **Bevel protractor**

Combination bevel protractor with blade and flat square.

Measuring range exterior angle: 0-180°.
Measuring range interior angle: 40-180°.

■ Reading: 1°.

■ Vernier reading: 2'.

■ Delivery in a case.



Item No.	Description	Price EUR
858.302	Bevel protractor	



### **Protractors**

- Semicircular head: 0 180° (with locking screw).
- Semicircular head: 10 170° (with locking screw and sliding blade).
- Hardened steel, no-glare chrome finished.
- Graduation placed by laser.



Item No.	Scale dia./mm	Blade length/mm	Price EUR
Semicircul	lar head 0 - 1	180°	
907.864	80	120	
907.865	120	150	
907.866	150	200	
907.867	200	300	
907.868	300	500	
Semicircul	lar head 10 -	· 170°	
907.869	100	150	
907.870	150	300	
907.871	200	400	
907.872	250	500	
907.873	300	600	

### **Protractor**

Simple and easy to use protractor with a semicircular head and swivelling blade.

- Semicircular head: 0 180° (with locking screw).
- Dial diameter: 85 mm.Length of blade: 150 mm.
- Hardened steel, no-glare chrome finished.

Item No. Description	Price EUR
907.863 Protractor	



ek bv

Measuring instruments and systems 2007/2008

345

### **Protractors**


Simple and easy to use protractors with a semicircular head and swivelling blade.


■ Measuring range: 0-180°.

Scale diameter: 85 mm.Blade length: 150 mm.

No-glare chrome finished steel.

Item No. Type/description	Price EUR
856.651 Protractor A 856.652 Protractor B	





### **Protractors**

- Measuring range: 0 180°.
- Scale diameter: 100 mm.
- Chrome finished stainless steel.



### **Protractors**

- Measuring range: 0-180° or 10-170° (with sliding blade).
- No-glare chrome finished steel.



Item No.	Scale	Blade	Price
	diameter	length	EUR
	mm	mm	
Measurii	ng range 0	- 180°:	
856.653	80	120	
856.654	120	150	
856.655	150	200	
856.656	200	300	
856.657	300	500	
856.658	400	600	
Measurii	ng range 10	) - 170°, wi	ith
sliding bl	ade:		
856.640	100	150	
856.641	150	300	
856.642	200	400	
856.643	250	500	
856.644	300	600	

© 2007, Schut Geometrische Meettechniek bv

346

Measuring instruments and systems 2007/2008